

# EUROMASK®

## FIBERGLASS TAPE EGC

**FINISHING GROUP S.R.L.**

### Features :

EGC is a 180 $\mu$  fiberglass tape with a 60 $\mu$  silicone adhesive 260°C resistant.

Recommended for thermal-spray and powder coating.

- Resistant to high pressure blasting
- Resistant to abrasion and solvents
- Flame Retardant



### Technical Data :

Carrier

Adhesive

Carrier Thickness (mm)

Total Thickness (mm)

Adhesion to Steel (N/25mm)

Tensile Strength (N/25mm)

Elongation (%)

Temperature Range (°C)

Tape Length (m)

### FIBERGLASS

Silicone

|             |                    |
|-------------|--------------------|
| ASTM D 1000 | <b>0.120</b>       |
| ASTM D 1000 | <b>0.180</b>       |
| ASTM D 1000 | <b>8.50</b>        |
| ASTM D 1000 | <b>525</b>         |
| ASTM D 1000 | <b>10</b>          |
| For 60'     | <b>-51 to +260</b> |
|             | <b>50</b>          |

NOTE: our recommendations are made in good faith and are based on our experience with this product. Since the conditions of use of this product are beyond our control, this data is given on the express condition and understanding that Finishing Group s.r.l. will not be liable to any person by reason thereof. Nothing herein shall be deemed to be a recommendation to use any product in violation of any existing patent right.