## EUROMASK®

## SILICONE RUBBER TAPE SRT25

## Features:

Silicone rubber tape without adhesive. Tape vulcanize on itself, forms an homogeneous cover that can withstand temperatures up to 300°C. Limited shelf life



## **Technical Data:**

Carriar

FINISHING GROUP S.R.L

Carrier		Silicone
Hardness Shore A	DIN 53 505	50
Specific Gravity (g/cm³)	DIN EN ISO 1183-1 A	1.19
Tensile Strength (N/mm²)	DIN 53 504 S 1	7
Elongation at Break (%)	DIN 53 504 S 1	590
Tear Resistance (N/mm)	ASTM D 624 B	21
Cure Conditions (°c) **	For 10'	+135

<sup>\*\*1,5%</sup> Curing agent E[=50 % paste of bis(2.4-dichlorobenzoyl)peroxide]

Tape Length (m)

NOTE: our recommendations are made in good faith and are based on our experience with this product. Since the conditions of use of this product are beyond our control, this data is given on the express condition and understeanding that Finishing Group s.r.l. will not be <u>liabale</u> to any person by reason thereof. Nothing herein shall be deemed to be a recommendation to use any product in violation of any existing patent right.

**FINISHING GROUP s.r.l.** Via B. Cellini, 6 – 20020 SOLARO (MI) - ITALIA Tel. +39 02 96780055 – Fax +39 02 96782993 – **N. VERDE 800.029.466** e-mail: <a href="mailto:info@euromask-shop.com">info@euromask-shop.com</a> - www.euromask-shop.com

25